

Heating, Ventilation & Signaling

Bath Fans

Fan/Light Combo

Square Fan with Light



- Efficient ventilation and bright light in one easy installation
- Fan and light operate separately or together
- Quiet operation with one-piece molded blower wheel and silent backdraft damper
- Attractive grille styling
- Plug-in motor and light
- Uses (1) 100 watt incandescent bulb (not included)

Dimensions: Housing: 9" X 9" X 5 3/4" Grille: 12" X 10 3/4"

Motor: Shaded pole, thermally protected

Part Number	CFM	Duct Diameter	Sones	Lamp Type
763RLNUTONE	50	4 in.	2.5	100 W Incandescent Max
769RLNUTONE	70	4 in.	3.0	100 W Incandescent Max

Recessed Fan/Light



- High efficiency centrifugal fan delivers 70 CFM, HVI-certified 1.5 Sones
- Trim matched to designs of major recessed light manufacturers
- Uses a 75 watt bulb, either R30 or BR30 for standard applications (not included)
- 6-7/8" high housing appropriate for new construction and 2" X 8" ceiling joists
- 4" round duct connector
- Not for use over cooking surfaces
- Type IC, Sealed Housing
- ENERGY STAR qualified

Part Number	CFM	Sones	Lamp	Lamp Type
744FLNTNUTONE	70	1.5	14W Fluor.	PL Lamp (Lamp Included)
744NTNUTONE	70	1.5	75W	R30 or BR30 (Not Included)

WhisperLite



Features:

- Energy efficiency and quiet operation, ENERGY STAR qualified
- Two 18-Watt compact fluorescent lamps and one 4-Watt night-lamp included
- Totally enclosed condenser motor for long life—rated for continuous run
- UL listed for tub/shower enclosure when used with a GFCI branch circuit wire
- Thermal fuse protection
- Electronic Ballast

Part Number	Fan Specifications			Lamp Specifications		
	CFM	Duct Diameter	Sones	Watts	Color	CRI
FV08VQL5PAN	80	4 in.	0.3	2 x 18W	3500	84
FV11VQL5PAN	110	4 in.	1.0	2 x 18W	3500	84

Quiet Test Fan-Light Night-Light



Features:

- 4" ducting
- Bright 100W incandescent lighting (bulb sold separately)
- 4W nightlight (bulb sold separately)
- UL Listed for use over tub/shower with GFCI circuit

Part Number	CFM	Sones	Ducting
QTRN110LNUTONE	110	1.5	4 in.

Bath Fans

Ventilation Fans

Deluxe Exhaust Fans



- Designed for large baths, utility rooms or laundry rooms
- Model 671R: For baths up to 85 sq. ft.; other rooms up to 110 sq. ft.
- Model 672R: For baths up to 105 sq. ft.; other rooms up to 135 sq. ft.
- Attractive Polymeric Grille fastens easily with torsion springs
- Prewired outlet box; plug-in receptacle
- Quiet plastic backdraft damper operates automatically

Dimensions: Housing: 9" X 9" X 5 3/4" deep Grille: 10 1/2" X 10 1/4" X 9/16"

Motor: Fully encased, plug-in, thermally protected, 115vAC, 60hZ Model 671R: 0.8 amp, Model 672R: 1.2 amp

Part Number	CFM	Sones	Duct Diameter
671RNUTONE	90	3.0	4 in.
672RNUTONE	110	4.0	4 in.

Ceiling/Wall Blower - 696N



- For baths up to 45 sq. ft., other rooms up to 60 sq. ft.
- Installs in ceiling or 2" X 4" wall studs
- Mounts on either 16" or 24" O.C. joist or stud

Dimensions: Housing: 7 1/2" long X 7 1/4" wide X 3 5/8" high Grille: 9 1/8" long X 8 3/4" wide X 1/2" thick

Motor: Shaded pole, thermally protected, 120vAC, 60 Hz, .9 amp

Part Number	CFM	Sones	Duct Diameter
696NNUTONE	50	4.0	3 in.

Replacement Parts - 696N



Part Number	Description
690RANUTONE	7 1/2" long X 7 1/4" wide x 3 5/8" high Bath Fan Housing Kit
696RNBUTONE	50 CFM, 4.0 Sones Finish Pack with Motor Assembly and Grille

Ceiling/Wall Mount Bathroom Fan - 695N



- For baths up to 65 sq. ft., other rooms up to 85 sq. ft .
- Plug-in motor, extra large junction box

Dimensions: Housing: 7 1/2" long X 7 1/4" wide X 3 5/8" high Grille: 9 1/8" long X 8 3/4" wide X 1/2" thick

Motor: Single coil thermally protected, 115vAC, 60 Hz, 1.2 amp

Part Number	CFM	Sones	Duct Diameter
695NUTONE	70	6.0	3 in.

Heating, Ventilation & Signaling

Bath Fans

Ventilation Fans

Ductless Ceiling/Wall Fan



Features:

- No duct required
- Install in ceiling or wall
- Activated charcoal filter helps keep air fresh
- White polymeric grille
- 1.0 Amp Rating

Part Number	Volts	Amps
682NTNUTONE	120	1.0

WhisperCeiling



Features:

- Energy efficiency and quiet operation, ENERGY STAR qualified
- Totally enclosed condenser motor for long life rated for continuous run
- UL listed for tub/shower enclosure when used with a GFCI branch circuit wire
- Thermal fuse protection

Part Number	CFM	Duct Diameter	Sones
FV08VQ5PAN	80	4 in.	0.3
FV11VQ5PAN	110	4 in.	0.8

Quiet Test Deluxe Exhaust Fans



Features:

- 4" ducting
- Motor engineered for continuous operation
- UL Listed for use over tub/shower with GFCI circuit
- Grille Dimension: 13" x 14"

Part Number	CFM	Sones	Bath Sq Ft	Ducting
QTRN080NUTONE	80	1.0	75	4 in.
QTRN110NUTONE	110	1.5	75	4 in.

Ventilation Fan with Heater & Light

Heat-A-Ventlite



- Three functions in one unit. Use them individually or together:
 1. 1300W heating element provides fast enveloping heat. Efficient fan evenly distributes warm air through room.
 2. 100W maximum lamp provides bright ceiling light (bulb not included).
 3. Efficient, quiet blower exhausts stale air and moisture to refresh the bath atmosphere
- Includes hanger bars, adjustable from 16"-24"

Dimensions: Housing: 14-5/8" X 7-7/8" X 5-5/8" Grille: 9-7/8" X 16-1/4" X 1-3/4"

Motor: Sleeve bearings, thermally protected, 120VAC, 60hZ, 12.5 A

Part Number	CFM	Duct Diameter	Sones	Description
665RPNUTONE	70	4 in.	4.0	12.5 Amp. Ventilation Fan with Heater & Light

Bath Fans

Ventilation Fan with Heater & Light

WhisperWarm



Features:

- A durable 1400-Watt steel sheathed heating element provides a quick warm up time
- Super quiet operation, Easy installation
- Totally enclosed condenser motor for long life- rated for continuous run
- Built-in damper to prevent backdraft
- Thermal fuse protection on motor and 3-level safety device for heater
- Quick 1 minute warm-up, 3 Year Warranty
- (2) 18 Watt Fluorescent Lamps and Nightlight included

Part Number	CFM	Duct Diameter	Sones	Description
FV11VHL2PAN	110	4 in.	0.7	Ceiling Mounted Fan/Heat/Light/Night-Light Combination

Conduit Bodies & Hazardous Location Fittings

Rigid/Aluminum Conduit Bodies, Covers & Gaskets

Malleable Conduit Bodies - Series 35

Gaskets - Series 35



Part Number	Description
GK50NSC	1/2" Neoprene Gasket for Rigid/IMC Series 35 Conduit Body
GK75NSC	3/4" Neoprene Gasket for Rigid/IMC Series 35 Conduit Body
GK100NSC	1" Neoprene Gasket for Rigid/IMC Series 35 Conduit Body
GK125-150NSC	1-1/4" - 1-1/2" Neoprene Gasket for Rigid/IMC Series 35 Conduit Body
GK200NSC	2" Neoprene Gasket for Rigid/IMC Series 35 Conduit Body
GK250-300NSC	2-1/2" - 3" Neoprene Gasket for Rigid/IMC Series 35 Conduit Body
GK350-400NSC	3-1/2" - 4" Neoprene Gasket for Rigid/IMC Series 35 Conduit Body